## State of California AIR RESOURCES BOARD

## EXECUTIVE ORDER A-4-206

Relating to Certification of New Heavy-Duty Motor Vehicle Engines

## NAVISTAR INTERNATIONAL TRANSPORTATION CORPORATION

Pursuant to the authority vested in the Air Resources Board by Sections 43100, 43102 and 43103 of the Health and Safety Code; and

Pursuant to the authority vested in the undersigned by Sections 39515 and 39516 of the Health and Safety Code and Executive Order G-45-9;

IT IS ORDERED AND RESOLVED: That the following 1998 model-year Navistar International Transportation Corporation diesel-cycle engines are certified for use in motor vehicles with a manufacturer's gross vehicle weight rating (GVWR) over 14,000 pounds:

Fuel Type: Diesel

Engine Family	Engine <u>Liters</u>	Displacement (Cubic Inches)	Exhaust Emission Control Systems and Special Features			
WNVXH0530CCB	8.7	(531)	Turbocharger Charge Air Cooler Engine Control Module Oxidation Catalytic Converter			

Engine models and codes are listed on attachments.

The following are the certification exhaust emission standards for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
1.3	15.5	4.0	0.10

The following are the certification exhaust emission values for this engine family in grams per brake horsepower-hour:

Total	Carbon	Nitrogen	<u>Particulates</u>
<u>Hydrocarbons</u>	<u>Monoxide</u>	<u>Oxides</u>	
0.1	4.0	4.0	0.08

BE IT FURTHER RESOLVED: That for the listed engine models, the manufacturer has submitted the materials to demonstrate certification compliance with the Board's emission control system warranty provisions (Title 13, California Code of Regulations, Section 2035 et seq.).

BE IT FURTHER RESOLVED: That the aforementioned engine family has been conditionally certified subject to the following conditions:

- 1. Any engine which employs a defeat device shall not be covered by this Executive Order.
- 2. Within 90 days following the issuance of this Executive Order, the manufacturer must show cause, to the satisfaction of the Executive Officer or his designee, that the strategy for fuel injection timing, including timing during the fuel economy mode, is not a defeat device.

Engines certified under this Executive Order must conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this order and attachments.

Executed at El Monte, California this 10 day of December 1997.

R. B. Summerfield, Chief

Mobile Source Operations Division

## LARGE ENGINE MOJEL SUMMARY

Manufacturer: Navistar A-4-206

Process Code: New Submission

EPA Engine Family: WNVXH0530CCB

Manufacturer Family Name:

**INT 530E** 

9.Emission Control 8.Fuel Rate:

	8.Fuel Rate: 9.Emission Control (Ibs/hr)@peak torque Device Per SAE J1930		DI, ECM, TC.	CAC, OC		DI, ECM, TC,	CAC, OC		DI, ECM, TC,	CAC, OC		DI, ECM, TC,	CAC, OC
	8.Fuel Rate; (lbs/hr)@peak tor		62.9			62.9			70.5			78	
IN SOUE	7.Fuel Rate: mm/stroke@peak torque		151.2			151.2			161.9			179	
	6.Torque @ RPM (SEA Gross)		800 @ 1300			800 @ 1300			860 @ 1300			950 @ 1300	
	5.Fuel Rate: (lbs/h) @ peak HP (for diesels only) 93				707	101		101			101		
	4.ruel Rate: mm/stroke @ peak HP (for diesel only)	430.0	0.05		150.0	0.001		150.0	0.001		150 B	0,00	
•	3.BHP@RPM (SAE Gross)	250 @ 2000	2007		275 @ 2000	2007		275 @ 2000	2007		275 @ 2000		
	2.Engine Model	A250C			AL275C			AF275C			A275C		
	1.Engine Code	A250C			AL275C			AF275C			A275C		